## Mobile conveyors Lokotrack CT3.2 and CW3.2

LOKOTRACK CT3.2 AND CW3.2



## Lokotrack CT3.2 and CW3.2 mobile conveyors

Track mounted Lokotrack CT3.2 and wheel mounted Lokotrack CW3.2 mobile conveyors offer an ideal solution for applications that require high stockpile capacity and excellent material transfer capabilities.

It also adds flexibility to multistage crushing and screening applications enabling easy and fast closed circuit operation of mobile units.

	42	
Specification		
	CT3.2	CW3.2
Capacity	400 mtph (440 stph)	400 mtph (440 stph)
Feed size up to	150 mm (6")	150 mm (6")
Belt width	1050 mm (42")	1050 mm (42")
Discharge height	9120 mm (29'11")	9120 mm (29'11")
Operational length	20 000 mm (65')	20 000 mm" (65')
Loading height	120 mm – 340 mm (4′0″ – 11′ 3″)	126 mm – 156 m (4'0" – 5' 3")
Engine	Caterpillar C2.2 38kw (51 HP)	-
Transport dir	mensions	
Length	Head section folded 13850 mm (45' 4")	12 200 mm (40' 3")
	Head and tail section folded 10610 mm (34' 10")	
Width	2350 mm (7'4")	2250 mm (7'4")
Height	Head section folded 2500 mm (8'2")	2500 mm (8'2")
	Head and tail section folded 2550 mm (8'4")	
Weight	9560 kg (21030 lbs)	6410 kg (14102 lbs)
Options		
	Hydraulic Folding of Tail Section Dual Hydraulic Drive for increased throughput	Hydraulic Folding Tail Section Hydraulic Folding Head Section Diesel – Hydraulic Power Unit Electric -Hydraulic Power Unit Dual Hydraulic Drive for increase throughput Chevron Belt



## The Metso Way — Making the big difference to our customers

Everything we do is based on deep industry knowledge and expertise that makes the big difference to our customers. Decades of close customer collaboration and adapting to our customers' ever changing needs have transformed us into a knowledge company.



