

M

REVISION						
ATE	DESCRIPTION					
9/21	523624GCP - RELEASE PER EM3233 MRY					

>	CRITICAL CHARACTERISTIC FOR PART SAFETY/COMPLIANCE						
)	DENOTES CRITICAL CHARACTERISTICS.						
K	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE						
5	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS.						
0	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE.						
EC			FINISH	FINISH			
DATE 4/14/20		DATE 4/14/2021	SCALE NTS		FINISH GOOD WT GRAMS/PIECE		
ESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS, DIMENSIONS IN TS [ ] ARE INCHES DIMENSIONING AND DO NOT INCLUDE PLATING. TOLERANCING TO BE INTERPRETED IN ACCORDANCE WITH ANSI Y14.5M-1994							
EV1K SERIES OUTLINE							
Littelfuse			REVISION	DRWG NO.	SHEET 1 OF 1 OUTLINE		
CHICAGO, ILLINOIS 60631			A	OL-EV1K000			